GREENBROOK

Datasheet: 20PME

Cable Management / Conduit Accessories

ME Lockring Plated 20mm



Technical Specification

Product Code	20PME
Feature 1	Mild Steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739612985
CE	Y
Colour	Bright Zinc
Company DUNS Number	216156018
Country of Origin	India
Finish body	Bright Zinc Plated
Fixings supplied with product	N
Galv Plating Thickness	>8µm
Greenbrook Guarantee (Years)	1
HS Code	7318190090
Installation method	Lock nut
Material Thickness	2.87

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/10/26

Datasheet: 20PME

Materials Main Body	Steel
Min Order Qty	100
Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	100
Package Product Max. Length (mm)	100
Package Product Max. Height (mm)	45
Package Product Max. Width (mm)	100
Package Product Weight gross (g)	728
Product (only) Max. Width (mm)	20 dia
Product Weight net (g)	0.007
Sales Pack Qty	100
Standards	BS EN 61386-21
StatusCode	Active
Thread Diameter	M20
Thread Diameter Ø	M20
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/10/26