GREENBROOK

Datasheet: 25GDS

## Cable Management / Conduit Accessories

# Distance Saddle Galv 25mm



## Technical Specification

| | |
|---|---|
| **Product Code** | 25GDS |
| **Feature 1** | Malleable Cast Iron |
| **Feature 2** | Conforms to BS EN 61386-21 |
| **Barcode** | 5012739609985 |
| **CE** | Y |
| **Colour** | Self Colour |
| **Company DUNS Number** | 216156018 |
| **Corrosion Test** | Y |
| **Country of Origin** | China |
| **Finish body** | Hot dip Galvanised |
| **Fixings supplied with product** | N |
| **Galv Plating Thickness** | >45µm |
| **Greenbrook Guarantee (Years)** | 1 |

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 28/10/26

# Datasheet: 25GDS

| | |
|---|---|
| **HS Code** | 7325991000 |
| **Installation method** | Surface mount |
| **Materials Main Body** | Malleable Iron |
| **Min Order Qty** | 25 |
| **Minimum Installation Temp** | -5 |
| **Operating Temperature Range max C** | 65 |
| **Operating Temperature Range min C** | -5 |
| **Pack Contents** | 25 |
| **Package Product Max. Length (mm)** | 240 |
| **Package Product Max. Height (mm)** | 85 |
| **Package Product Max. Width (mm)** | 160 |
| **Package Product Weight gross (g)** | 2099 |
| **Product (only) Max. Width (mm)** | 25 dia |
| **Product Weight net (g)** | 18.5 |
| **Sales Pack Qty** | 25 |
| **StatusCode** | Active |
| **UKCA** | Y |
| **Working Temperature** | -5 to 65 C |

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 28/10/26