GREENBROOK

Datasheet: 32PME

Cable Management / Conduit Accessories

ME Lockring Plated 32mm



Technical Specification

Product Code	32PME
Feature 1	Mild Steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739614149
CE	Y
Colour	Bright Zinc
Company DUNS Number	216156018
Country of Origin	India
Finish body	Bright Zinc Plated
Fixings supplied with product	N
Galv Plating Thickness	>8µm
Greenbrook Guarantee (Years)	1
HS Code	7318190090
Installation method	Lock nut
Material Thickness	2.87

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/10/26

GREENBROOK

Datasheet: 32PME

Materials Main Body	Steel
Min Order Qty	100
Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	50
Package Product Max. Length (mm)	145
Package Product Max. Height (mm)	70
Package Product Max. Width (mm)	114
Package Product Weight gross (g)	1584
Product (only) Max. Width (mm)	32 dia
Product Weight net (g)	14.5
Sales Pack Qty	100
Standards	BS EN 61386-21
StatusCode	Active
Thread Diameter	M32
Thread Diameter Ø	M32
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/10/26