GREENBROOK

Datasheet: 4PME

Cable Management / Conduit Accessories

ME Lockring Plated 1.5"



Technical Specification

Product Code	4PME
Feature 1	Mild Steel
Feature 2	Conforms to BS EN 61386-21
Barcode	5012739614798
CE	Y
Colour	Bright Zinc
Company DUNS Number	216156018
Country of Origin	India
Finish body	Bright Zinc Plated
Fixings supplied with product	N
Galv Plating Thickness	>8µm
Greenbrook Guarantee (Years)	1
HS Code	7318190090
Installation method	Lock nut
Material Thickness	2.87
Materials Main Body	Steel

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/10/26

Datasheet: 4PME

Min Order Qty	50
Minimum Installation Temp	-5
Operating Temperature Range max C	65
Operating Temperature Range min C	-5
Pack Contents	50
Package Product Max. Length (mm)	150
Package Product Max. Height (mm)	65
Package Product Max. Width (mm)	115
Package Product Weight gross (g)	1123
Product (only) Max. Width (mm)	1.5 inch dia
Product Weight net (g)	22
Sales Pack Qty	50
Standards	BS EN 61386-21
StatusCode	Active
Thread Diameter	1.5 inch
Thread Diameter Ø	1.5 INCH
UKCA	Y
Working Temperature	-5 to 65 C

Tel No: 01279 772 772
Email: sales@greenbrook.co.uk
Website: www.greenbrook.co.uk

This document is uncontrolled if printed, all information is subject to change. Generated on 26/10/26