

Circuit Protection / MK Sentry

RCBO 10A 30MA SINGLE MODULE TYPE B A STYLE



Technical Specification

Product Code	H6833S
Breaking Capacity (kA)	6000
Country of Origin	CHINA
Degree of Pollution	2
IP Rating	IP20
Maximum Installation Altitude (m)	2000
Maximum Operating Temperature (°C)	55
MCB Curve	B
Minimum Operating Temperature (°C)	-5
Number of Modules	1
Number of Poles	1P SOLID NEUTRAL
Operation Frequency (Hz)	50-60
Pack Quantity	1
Package Product Max. Length (mm)	150

Package Product Max. Depth (mm)	82
Package Product Max. Width (mm)	26
Package Weight (kg)	0.02
Packaging Material	CARDBOARD - RECYCLED
Product (only) Max. Depth (mm)	71
Product (only) Max. Height (mm)	114
Product (only) Max. Width (mm)	18
Product Weight (kg)	0.15
Rated Impulse Withstand Voltage (v)	40000
Rated Operational Current (A)	10
Rated Operational Voltage (v)	230
Rated Tripping Current (mA)	30
RCD Type	A
Standards	BSEN61009-1 / 2- 2,BS61543
Terminal Capacity L-In (mm ²)	25
Terminal Capacity L/N-Out (mm ²)	10
Tightening Torque (Nm)	2.5

Tel No: 01279 772 772

Email: sales@greenbrook.co.ukWebsite: www.greenbrook.co.uk