




General Information

Dimensions (mm)	114 (W) 53 (D) 136 (H)
Materials	Body: Powder Coated Aluminium; Diffuser: Polycarbonate
Colour	Black
Product Weight (Kg)	0.18
Ingress Protection	IP65
Impact Rating (IK)	06
Flammability Rating	UL94-V2
Mounting	Wall
Warranty (Years)	3

Supply & Power Information

Continuous Operating Voltage (AC) (Hz)	220-240 (50)
Safety Class	I
Circuit Wattage (W)	20
Input Current (mA)	87
Inrush Current/Time	5.78A (0.056ms)
Power Factor	>0.8
Operating Temperature (°C)	-20 to +40
Input Mains Cable	3 x 1mm ² H05RN-F (1 Metre)

Luminaire Output

Colour Temperature (K)	4000
Colour Render Index (CRI)	>80
Typical Luminous Flux (lm)	1800
Efficacy (lm/W)	90
Beam Angle (°)	100
LED Lifetime (L70) (Hours)	20000

Sensor Information

Maximum Mounting Height (m)	2.5
Detection Distance (m)	8
Detection Angle (°)	120
Light Level Settings (Lux)	10 to 2000
Time Delay Settings	10 Secs to 3 Mins

Dimming Information

Dimmable	No
----------	----

