SPECIFICATION

SELECT

Selene 2 LED Panel

3CCT, 2 Power, TP(b)

Beam Angle
110°

Input
220-240V

Life Hours
50000

Dimmable
No

Colour Temperature
3000K 4000K 6500K

	600 x 600	600 x 600	1200 x 600	1200 x 300
Part Number	**SE2B-28N**	**SE2B-36T**	**SE2B-126T**	**SE2B-123T**
Tp Rating	Tp(b)	Tp(b)	Tp(b)	Tp(b)
Selectable Power	28W	25/36W	38/56W	25/36W
Max Power	28W	26W	56W	36W
Max Lumens	3480	3600	5800	3800
Dimensions (mm)	595x595x32	595x595x32	1195x595x33	1195x295x33
CCT (Kelvin)	4000	3000/4000/6500	3000/4000/6500	3000/4000/6500
Order Multiples	6	1	1	1
Surface Mounting Kits	**SE2-CWM66**	**SE2-CWM66**	**SE2-CWM126**	**SE2-CWM123**
Selt Test Emergency Kit	**SE-EM3W**			
Panel Power	3-100W			
Output V	9-80W			
Output A	30-70mA			

Key Features

- Selectable 3 colour temperatures
- Selectable Power Option
- Back Lit Panel
- Self Test Emergency Available
- Flicker free
- Surface Mount Kits Available
- 5 year warranty

CRI >80 IP 40 Emergency

Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.