DATASHEET



CPLEM

230V CPL Downlight Emergency Kit

www.mlaccessories.co.uk

MLA PART CODE	**CPLEM**
DESCRIPTION	230V CPL Downlight Emergency Kit
NET WEIGHT (KG)	0.34
FINISH	White
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
INPUT VOLTAGE	230V 50Hz
DIMENSIONS (MM)	Length - 211 Height - 24 Width - 34 Recessed Depth - 0 Minimum Void - 50
CUT-OUT (MM)	Cut-out Diameter - 46 Min./Max. Cut-out - Min. 46
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	Manual
IC RATED	No
WATTAGE (W)	5.5
LAMP INCLUDED	No
BATTERY TYPE	LiFePO4
BATTERY INCLUDED	Yes
DRIVER	MAX. OUTPUT - 5.5W OUTPUT VOLTAGE - 230V POWER FACTOR - 0.7 AMBIENT TEMPERATURE (Ta) - 0-45°C CASE TEMPERATURE (Tc) - 70°C
WARRANTY	3year(s)
WARRANTY INFORMATION	(excluding battery)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598-2-22
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270809206

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

Knightsbridge

Date Created: 21/10/2026 11:43

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.