



## DATASHEET



### UCLCT18

230V 18W LED Linkable Striplight CCT Adjustable (1138mm)

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



| MLA PART CODE                 | UCLCT18                                                  |
|-------------------------------|----------------------------------------------------------|
| DESCRIPTION                   | 230V 18W LED Linkable Striplight CCT Adjustable (1138mm) |
| NET WEIGHT (KG)               | 0.407                                                    |
| FINISH                        | White                                                    |
| DIFFUSER                      | Opal                                                     |
| DIMENSIONS (MM)               | Length - 1138<br>Width - 22.8<br>Projection - 36         |
| CONSTRUCTION                  | Construction - Polycarbonate                             |
| CLASS                         | II                                                       |
| IP RATING                     | IP20                                                     |
| WATTAGE (W)                   | 18                                                       |
| LAMP TECHNOLOGY               | LED                                                      |
| LAMP INCLUDED                 | Yes                                                      |
| LUMENS (LM)                   | 1675 / 1915 / 1780                                       |
| LUMENS LIGHT SOURCE ONLY (LM) | 1840                                                     |
| LUMEN TOLERANCE               | 5%                                                       |
| EFFICACY (LM/W)               | 107.9                                                    |
| CIRCUIT WATTAGE (W)           | 17.1                                                     |
| CCT                           | 3000/4000/6500K                                          |
| LIGHT COLOUR                  | CCT                                                      |
| CRI                           | >80                                                      |
| SDCM                          | <6                                                       |
| RUNNING CURRENT (A)           | 0.125                                                    |
| DISPLACEMENT FACTOR           | >0.9                                                     |
| SVM                           | 0.03                                                     |
| PST-LM                        | 0.013                                                    |
| BEAM ANGLE (DEGREES)          | 140                                                      |
| LIFE SPAN (HRS)               | 30,000                                                   |
| L70B50 LIFESPAN (HRS)         | 54,000                                                   |

|                                          |               |
|------------------------------------------|---------------|
| DIMMABLE                                 | No            |
| OPERATING TEMPERATURE                    | -10~40°C      |
| INPUT VOLTAGE                            | 230V 50Hz     |
| WARRANTY                                 | 2year(s)      |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598   |
| ORIGIN OF MANUFACTURE                    | China         |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes           |
| EAN                                      | 5055832999645 |

Date Created: 22/09/2022 16:26

